



## LCS2650-BR Broadcast LCD Monitor

### Detailed Specifications

<b>Model</b>	LCS2650-BR	
<b>Cabinet Color</b>	Black	
<b>Display</b>	Type	Super MVA TFT AM-LCD
<b>Display Area</b>	Diagonal	26" (685.8mm)
	Horizontal	22.79" (578.8mm)
	Vertical	12.87" (326.8mm)
	Resolution	1920 x 1200
	Pixel Pitch	N/A
	Aspect Ratio	16:9
	Luminance	500 cd/m <sup>2</sup> (typical)
	Contrast Ratio	1500:1 (typical)
<b>Viewing Angle</b>	Horizontal	176°
	Vertical	176°
<b>Response Time</b>		6.5ms (G to G)
<b>Picture</b>	Display Modes	Composite, Component, S-Video, DVI, PC
	Color Temperature	User, 3200K, 6500K, 7500K, 9300K, SMPTE
	Image Size	1:1, Fill, Aspect, Panoramic
	Gamma Correction	Off, 2.2, 2.4
	PIP Mode	Off, Single, PAP
	PIP Size	Small, Medium, Large
<b>Additional Features</b>		Angle Filtering, Black Level Control, Ambient Light Sensor Variable Back Light Control, Cadence Detection, Noise Reduction
<b>OSD</b>	Type	Color
	Language	English
<b>Terminals</b>	Video	RCA Jack x 1
	S-Video	Y/C x 1
	Component	YPbPr x 1 (8p DIN)
	RGB (PC)	D-sub 15pin
	RS232	D-sub 9pin
	DVI	D-sub 24pin
<b>Compatibility</b>	Color System	NTSC
	Video System	NTSC
	PC/Mac	VGA/SVGA/XGA/WXGA
	Digital	VGA/SVGA/XGA/WXGA
	SDTV/EDTV/HDTV	480i/576i/720p/1080i
<b>Scan Rate</b>	Horizontal	30– 65 KHz
	Vertical	56 – 75 Hz
<b>Power</b>	Input Voltage	AC 100-240V, 50/60Hz
<b>Power Consumption</b>	During Operation	110W (Max)
	Stand by	11W (Max)
<b>Power Management</b>		VESA DPMS, DVI DMPM
<b>Monitor Dimensions</b>	With Stand	25.93"(W) x 17.52"(H) x 6.33"(D)
	Without Stand	25.93"(W) x 15.98"(H) x 3.77"(D)
	Carton Box Dimensions	30.32"(W) x 22.45"(H) x 11.25"(D)
<b>Weight</b>	Monitor Weight	27.63lbs (12.5Kg)
	Shipping Weight	36.47lbs (16.5Kg)
<b>Environmental</b>	Operating Temp	41° to 104°F (5° to 40°C)
	Op. Humidity	20 - 85%
	Storage Temp	-4° to 140°F (-20° to 60°C)
<b>Regulations</b>	Safety	UL, cUL, TUV/PS, ROHS/WEEE
	EMC	FCC, CE, VCCI, BSMI, CCC, CB
<b>Wall Mount</b>		VESA 200mm x 200mm
<b>Included Accessories</b>		Power cord, User's manual, Remote control, RCA cable DVI-D 24 pin cable, D-SUB 15pin cable, S-VIDEO Mini Din 4 pin cable Component Mini Din 8 pin cable
<b>Optional Accessories</b>		Tempered Glass
<b>Warranty</b>		1 Year Parts and Labor

Specifications, features and design are subject to change without notice