

LCS2650-BR


37 INCH HIGH DEFINITION BROADCAST GRADE LCD MONITOR
-with RS232C



The LCS2650-BR High Definition LCD Monitors is specifically designed for Broadcast, Post-Production, Broadcast Truck and Video Editing applications. This monitor is factory calibrated to the SMPTE C / 709 Standard and is configurable for SDI and HD-SDI operation (option). The LCS2650-BR also has an integrated safe zone generator for both 4:3 and 16:9 applications. This monitor is designed specifically for the rigors of the broadcast and production environments as well as extended operation applications. The LCS2650-BR LCD Monitor is a highly configurable version with advanced video processing, RS232C, tempered glass, Audio In/Out or HD-SDI In/Out. .

Features

- Variable Black Level Adjustment
- Variable Back Light Adjustment
- Advanced Video Processing
- Durable Metal Construction
- Picture in Picture, Picture and Picture
- AutoAmbient Brightness Compensation
- Fanless Design for Quiet Operation
- Anti-Reflective Coated LCD panels
- 176+ Degree H / V Viewing Angle
- Infrared and RS232 Control
- VESA Mounting Hole Pattern
- Approvals: cUL / FCC
- One Year Parts & Labor Warranty
- Extended Warranties Available



Specifications

Technology: TFT LCD
 Screen diagonal: 26" (686 mm)
 Screen area: 23.74" x 13.46" (578.8 x 326.8 mm)
 Resolution: 1920 x 1200p
 Brightness: 500 cd/m2
 Contrast ratio: 1500:1
 Colors: 16.7 million
 Lifetime : 50,000h average
 Color gamut: 76% NTSC
 Aspect ratio: 16:9
 Viewing angle: H160°/V150°
 Response time: 6.5ms GtoG
 Color Control: 3200K-9300K, SMPTE

Inputs: DVI-D, VGA (D15), S-Video, Composite Video, Component video (YPbPr, YCbCr)
 Resolutions Supported: NTSC/PAL/SECAM , 720i/p, 1080i/p, XGA, WXGA, SXGA, RS232C
 Control: VESA 200x200mm
 Mounting: VESA 200x200mm
 Voltage: 100 - 240V (50Hz-60Hz)
 Power Consumption: <110W (On) <11W Stand-By
 Operating Temp: 41° to 104°F (5° to 40°C)
 Op. Humidity: 20 - 85%

Compliance: FCC, CE, cUL
 Weight: 27.63lbs (12kg)
 Gross Weight: 36.47lbs (16kg)

Included Accessories:
 Power cord, D-SUB 15pin cable , DVI-D 24 pin cable S-VIDEO cable, Component Mini Din 8 pin cable, RCA cable, Remote control, User's manual

OPTIONS

- Tempered Glass
- Bottom or Side Speakers
- HD-SDI Input
- Audio Amp
- Open Frame Versions Available