

Broadcast LCD Monitors

The Ovideon LCS Series High Definition Broadcast LCD Monitors are specifically designed for Broadcast, Post-Production, Broadcast Truck and Video Editing applications. These monitors are factory calibrated to the SMPTE C or 709 Standard and are configurable for SDI and HD-SDI (option) operation.

- 26** **LCS2650-BR**
26 inch Diagonal
- Resolution: 1920x1200p
 - Brightness: 500 CD/M2
 - Contrast Ratio: 1200:1
 - 6.5ms Response Time
 - RS232C



- 37** **LCS3730-BR**
37 inch Diagonal
- Resolution: 1920x1080p
 - Brightness: 500 CD/M2
 - Contrast Ratio: 1200:1
 - 6.5ms Response Time
 - RS232C



- 42** **LCS4230-BR**
42 inch Diagonal
- Resolution: 1920x1080p
 - Brightness: 500CD/M2
 - Contrast Ratio: 1200:1
 - 6.5ms Response Time
 - RS232C



- 47** **LCS4730-BR**
47 inch Diagonal
- Resolution: 1920x1080p
 - Brightness: 500 CD/M2
 - Contrast Ratio: 1200:1
 - 6.5ms Response Time
 - RS232C



- 52** **LCS5230-BR**
52 inch Diagonal
- Resolution: 1920x1080p
 - Brightness: 500 CD/M2
 - Contrast Ratio: 1500:1
 - 6.5ms Response Time
 - RS232C



- 57** **LCS5730-BR**
57 inch Diagonal
- Resolution: 1920x1080p
 - Brightness: 500 CD/M2
 - Contrast Ratio: 1500:1
 - 6.5ms Response Time
 - RS232C



Common Features

- Variable Black Level Adjustment
- Variable Back Light Adjustment
- Picture in Picture, Picture and Picture
- AutoAmbient Brightness Compensation
- Fanless Design for Quiet Operation
- Anti-Reflective coated LCD panels
- Composite and S-Video input
- 15 Pin VGA and DVI-D Input
- Auto "No Signal" Power Off
- 176+ Degree H / V Viewing Angle
- Infrared and RS232 Control
- VESA Mounts 100/200MM
- Power: 100~240V AC 50/60HZ
- Approvals: cUL / FCC / CE
- One Year Parts & Labor Warranty
- Extended Warranties Available

OPTIONS

- Protective Glass
- Bottom Speakers
- HD-SDI Input Card
- Audio Amp Card

